



Standard brake designed for 1.18" disc thickness

DISC DIAMETER	C/L FRICTION DIAMETER	MAX HUB DIAMETER	THRUSTER TYPE				
			ED121	ED201	ED301		
D1	D2	H1	W1	X1	TORQUE (LbFt)	TORQUE (LbFt)	TORQUE (LbFt)
19.70	15.70	5.25	21.58	4.700	900 – 2200	1400 – 3400	1900 – 4800
21.00	17.00	6.50	22.23	5.350	900 – 2300	1500 – 3700	2100 – 5200
22.00	18.00	7.50	22.73	5.850	1000 – 2500	1600 – 3900	2200 – 5600
24.00	20.00	9.50	23.73	6.850	1100 – 2700	1700 – 4300	2500 – 6200
24.80	20.80	10.30	24.13	7.250	1200 – 2900	1800 – 4500	2600 – 6400
28.00	24.00	13.50	25.73	8.850	1300 – 3300	2100 – 5200	3000 – 7400
29.00	25.00	14.50	26.23	9.350	1400 – 3400	2200 – 5400	3100 – 7700
31.50	27.50	17.00	27.48	10.600	1500 – 3800	2400 – 6000	3400 – 8500
34.00	30.00	19.50	28.73	11.850	1600 – 4100	2600 – 6500	3700 – 9300
35.40	31.40	20.90	29.43	12.550	1700 – 4300	2700 – 6800	3900 – 9700
38.00	34.00	23.50	30.73	13.850	1900 – 4700	3000 – 7400	4200 – 10500
39.40	35.40	24.90	31.43	14.550	2000 – 4900	3100 – 7700	4400 – 10900
49.20	45.20	34.70	36.33	19.450	2500 – 6200	3900 – 9800	5600 – 14000
50.00	46.00	35.50	36.73	19.850	2500 – 6300	4000 – 10000	5700 – 14200

WGT (Lbs)

580

580

582

All dimensions are shown in inches