

# SBP2® PENDANT PUSHBUTTON STATIONS

The Lightweight Pendant Solution for Heavyweight Applications

IDEAL FOR  
**FLUID  
POWER**  
APPLICATIONS



SBP2® Pendant Pushbutton Stations provide optimum control and performance for vehicle mounted machinery. It's DC rating eases integration into a wide variety of mobile equipment, including mobile cranes, vacuum trucks, stacker conveyors, trenchers, grinders, concrete mixers, pumpers, and pavers. SBP2 allows the operator a wide range of movement, providing improved machine visibility and handling. Most models weigh less than two pounds, and this slim-line pendant's lightweight design rests comfortably in the palm of your hand.

## RELIABILITY & CONVENIENCE

- Ergonomic design – offers comfortable control and performance with less effort and fatigue than traditional pendants
- Superior durability – designed to survive even the most brutal environments, and the high-impact resistant, watertight enclosure is ideally suited for many applications
- Quick delivery – many stock SBP2 Pendants are available and can be shipped the same day

## FLEXIBLE & DEPENDABLE PERFORMANCE

- 2, 4, 6, 8, 10 or 12 button configurations
- Suitable for AC or DC applications
- Switches are rated 2 Amp, 24 VDC, and 3 Amp, 250 VAC
- 1, 2 or 3 speed operation
- Impact resistant pendant enclosure is double insulated, chemically resistant and rated NEMA 1, 3, 4, 4X and 12
- Cable grip clamps provide a watertight sealed connection between cable and enclosure
- Switches are protected from internal/external contaminants
- Common circuit is pre-wired on all switches to simplify wiring
- Mechanical interlocks on single- and two-speed switches for enhanced safety
- Cumulative contacts on two- and three-speed switches provide precise detent feel
- Easy-to-read button functions
- Operating temperature range: -10°F to 150°F
- UL listed, CSA approved

## CUSTOM CAPABILITIES

- Maintained two button on/off (instead of standard momentary on/off)
- Single speed switch inserts with one normally closed (N.C.) and one normally open (N.O.) contact per button
- Pilot light (mounting in upper left hand accessory hole and/or standard button hole)
- On/off key switch
- Red mushroom on/off switch
- Blanks to cover button holes
- Two and three position selector switches
- Pre-wired with or without quick disconnect
- Other custom configurations are available – consult factory

For more information, contact your local Magnetek Sales Representative, [radio.sales@magnetek.com](mailto:radio.sales@magnetek.com), or the Magnetek location nearest you.



**MAGNETEK**



[WWW.MAGNETEK.COM](http://WWW.MAGNETEK.COM) | [RADIO.SALES@MAGNETEK.COM](mailto:RADIO.SALES@MAGNETEK.COM)

HEADQUARTERS  
N49 W13650 Campbell Drive  
Menomonee Falls, WI 53051  
Toll-Free Phone 800.288.8178  
Toll-Free Fax 800.298.3503  
Phone 1.262.783.3500  
Fax 1.262.783.3510

CANADA FACILITY  
161 Orندا Road, Unit 1  
Brampton, Ontario  
L6W 1W3 CANADA  
Toll-Free Phone 800.792.7253  
Phone 905.828.1526  
Fax 905.828.5707

UK FACILITY  
Unit 3, Bedford Business Centre  
Mile Road  
Bedford MK42 9TW UK  
Phone +44 (0)1234 349191  
Fax +44 (0)1234 268955

